Tunnel Ladder FPT EU 2.3

Technical Data Sheet

Product Code	F-LAD FPT EU 2.3
Manufacturer's Name	Branach Manufacturing Pty Ltd
Phone Number	+61 3 9761 6633
Certified By (Name, Title)	Mike Walsh Chief Design Engineer
Last Updated	03/06/2025

PROPERTIES

$\mathbf{\nabla}$	Standards	Engineered Modified Product based on: EN131-7
Â	Load Rating	150 kg
4	Electrical Properties	Non-conductive
J	Heat Resistance	130 Degrees Celsius
Ø	Warranty	3 years from date of manufacturing

COMPONENTS

COMPONENTS		
A	Stiles	Fibreglass: ISO-PE resin with e-glass fibres
в	Rungs	Round: Alloy 6060 / Mg 0.35-0.6 / Ti 0.10%
С	Feet	Thermoplastic Polyurethane
D	Platform Deck	Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0%
E	Platfrm Hooks	Alloy 5083/H116 / Mg 4.0-4.9 / Ti 0-0.15%
F	Handrail	Alloy 6463-T6 / Mg 0.3-0.9 / Ti 0%
G	Brackets	Alloy 5083 /H116 4.0-4.9 / Ti 0-0.15%
Н	Rods and Struts	Alloy 6463-T6 / Mg 0.3-09 / Ti 0%
	Spacer	Polyethylene
J	Step Plates	Alloy 5052 H32 / Mg2.2-2.8 / Ti 0%
	Rivets	Zinc Plated, Trivalent Chromate Passivation
	Nuts	Plated Mild Steel with gold passivate
	Washers	Plated Mild Steel with gold passivate

MEASUREMENTS

Adjustable 50mm - 860mm

kg	Weight	29.2kg
₹	Distance Between Rungs	300mm
\$	Open Height	3.26m
≽	Closed Height	3.43m
⊼	Platform Height	2.29m
Γ	Handrail Height	0.96m above platform
-	Leg length	1.54m
Х	Closed Width	0.55m
Ч	Number of steps	8 (including platform)



С

