



EuroMaster All Terrain Step Platform FPE-AT 2.3

Technical Data Sheet

PROPERTIES	
Standards	BS EN 131-7:2013 / AS/NZS 1892.3 / ANSI A 14.5-2000
Load Rating	150kg
Electrical Properties	Complies to AS/NZS 1892.3 Section 2.4
Heat Resistance	130 Degrees Celsius
Chemical Resistance	Tested to AS/NZS 1892.3
Accelerated Weathering Test	Tested to AS 2331.3.1
Warranty	3 years from date of manufacturing

MEASUREMENTS	
Weight	36.0kg
Distance Between Rungs	0.300m
Open Height	3.25m
Closed Height	3.72m
Platform Height	2.29m
Handrail Height	0.96m above platform
Closed Width	0.22m
Width with Stabilisers	1.75m (Fully extended)
Number of Steps	8 including platform

COMPONENTS	
Stiles	Fibreglass: ISO-PE resin with e-glass fibres
Rungs	Round: Alloy 6060 / Mg 0.35-0.6 / Ti 0.10%
Feet	Thermoplastic Polyurethane
Platform Deck	Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0%
Platform Hooks	Alloy 5083-H116 / Mg 4.0-4.9 / Ti 0-0.15%
Handrail	Alloy 6463-T6 / Mg 0.3-0.9 / Ti 0%
Brackets	Alloy 5083-H116 / Mg 4.0-4.9 / Ti 0-0.15%
Rods and Struts	Alloy 6463-T6 / Mg 0.3-0.9 / Ti 0%
Spacer	Polyethylene
Step Plates	Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0%
Rear Step	Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0%
Rivets	Zinc Plated, Trivalent Chromate Passivation
Nuts	Zinc Plated, Trivalent Chromate Passivation
Washers	Zinc Plated, Trivalent Chromate Passivation

Product Code	FPE-AT 2.3
Manufacturer's Name	Branach Manufacturing Pty Ltd
Phone Number	+61 3 9761 6633
Certified By (Name, Title)	Mike Walsh Chief Design Engineer
Last Updated	4/04/2025



Note: May only be used in fully extended position.