

# Fibreglass Rung Extension FEY 6.4

## Technical Data Sheet

Product Code	FEY 6.4
Manufacturer's Name	Branach Manufacturing Pty Ltd
Phone Number	+61 3 9761 6633
Certified By (Name, Title)	
Last Updated	

### PROPERTIES

<input checked="" type="checkbox"/> Standards	AS/NZS 1892.3
<input checked="" type="checkbox"/> Load Rating	150kg
<input checked="" type="checkbox"/> Electrical	Complies to AS/NZS 1892.3 Section 2.4
<input checked="" type="checkbox"/> Heat Resistance	130 Degrees Celsius
<input checked="" type="checkbox"/> Warranty	3 years from date of manufacturing
<input checked="" type="checkbox"/> Chemical Resistance	Tested to AS/NZS 1892.3
<input checked="" type="checkbox"/> Accelerated Weathering Test	Tested to AS 2331.3.1

### MEASUREMENTS

<input checked="" type="checkbox"/> Weight	21.4kg
<input checked="" type="checkbox"/> Distance Between Rungs	0.305m
<input checked="" type="checkbox"/> Closed Height	4.00m
<input checked="" type="checkbox"/> Extended Height	6.40m
<input checked="" type="checkbox"/> Width	Fly: 0.370m / Base: 0.450m

### LADDER COMPONENTS

<b>A</b> Stiles	Fibreglass: ISO-PE resin with e-glass fibres
<b>B</b> Rungs	Round: Fibreglass ISO-PE resin with e-glass fibres
<b>C</b> Feet	Swivel: 35% GF Nylon
<b>D</b> Rung Wear Strip	HD Polyethylene
<b>E</b> End Caps	35% GF Nylon PV 35H
<b>F</b> Rope	Polypropylene 10mm
<b>G</b> Latch	Aluminium 6106 T5 and steel plated
<b>H</b> Ladder Guide Bracket	50mm Alum 6060, E coat & black powder coat
<b>I</b> Running Guide Bracket	XF 400 Steel zinc plated with gold passivate
<b>J</b> Tie Down Bar	Steel zinc plated, gold passivate
Rivets	Zinc plated low carbon steel

