

Fibreglass Rung Extension FEY 8.8

Technical Data Sheet

| | |
|-------------------------------|-------------------------------|
| Product Code | FEY 8.8 |
| Manufacturer's Name | Branach Manufacturing Pty Ltd |
| Phone Number | +61 3 9761 6633 |
| Certified By (Name, Title) | |
| Last Updated | |

PROPERTIES

| | |
|---|---------------------------------------|
| <input checked="" type="checkbox"/> Standards | AS/NZS 1892.3 |
| <input checked="" type="checkbox"/> Load Rating | 150kg |
| <input checked="" type="checkbox"/> Electrical | Complies to AS/NZS 1892.3 Section 2.4 |
| <input checked="" type="checkbox"/> Heat Resistance | 130 Degrees Celsius |
| <input checked="" type="checkbox"/> Warranty | 3 years from date of manufacturing |
| <input checked="" type="checkbox"/> Chemical Resistance | Tested to AS/NZS 1892.3 |
| <input checked="" type="checkbox"/> Accelerated Weathering Test | Tested to AS 2331.3.1 |

MEASUREMENTS

| | |
|--|----------------------------|
| <input checked="" type="checkbox"/> Weight | 31.2kg |
| <input checked="" type="checkbox"/> Distance Between Rungs | 0.305m |
| <input checked="" type="checkbox"/> Closed Height | 5.20m |
| <input checked="" type="checkbox"/> Extended Height | 8.80m |
| <input checked="" type="checkbox"/> Width | Fly: 0.370m / Base: 0.450m |

LADDER COMPONENTS

| | |
|--------------------------------|--|
| A Stiles | Fibreglass: ISO-PE resin with e-glass fibres |
| B Rungs | Round: Fibreglass ISO-PE resin with e-glass fibres |
| C Feet | Swivel: 35% GF Nylon |
| D Rung Wear Strip | HD Polyethylene |
| E End Caps | 35% GF Nylon PV 35H |
| F Rope | Polypropylene 10mm |
| G Latch | Aluminium 6106 T5 and steel plated |
| H Ladder Guide Bracket | 50mm Alum 6060, E coat & black powder coat |
| I Running Guide Bracket | XF 400 Steel zinc plated with gold passivate |
| J Tie Down Bar | Steel zinc plated, gold passivate |
| Rivets | Zinc plated low carbon steel |

