## WorkMaster 450mm Step Platform FPL-AT 2.4

## **Technical Data Sheet**

PROPERTIES	
Standards	AS/NZS 1892.3 / ANSI A 14.5-2000
Load Rating	150kg
Flectrical Properties	Complies to AS/NZS 1892.3 Section 2.4
Heat Resistance	130 Degrees Celsius
Chemical Resistance	Tested to AS/NZS 1892.3
Accelerated Weathering Test	Tested to AS 2331.3.1
🛱 Warranty	3 years from date of manufacturing

## MEASUREMENTS

kg	Weight	28kg
₹	Distance Between Rungs	0.305m
٥	Open Height	3.23m
≽	Closed Height	3.52m
⊼	Platform Height	2.4m
Γ	Handrail Height	0.9m above platform
⋗	Closed Width	0.2m
K	Width with Satbilisers	Extended 0.93m/Fully Extended 1.32m
۲	Number of Steps	8 including platform

## COMPONENTS

~~	COMI ONEINS		
A	Stiles	Fibreglass: ISO-PE resin with e-glass fibres	
в	Rungs	Round: Alloy 6060 / Mg 0.35-0.6 / Ti 0.10%	
С	Feet	35% GF Nylon / Poly Urethane Tread	
D	Platform Deck	Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0%	
E	Platform Hooks	Alloy 5083-H116 / Mg 4.0-4.9 / Ti 0-0.15%	
F	Handrail	Alloy 6463-T6 / Mg 0.3-0.9 / Ti 0%	
G	Brackets	Alloy 5083-H116 / Mg 4.0-4.9 / Ti 0-0.15%	
н	Rods and Struts	Alloy 6463-T6 / Mg 0.3-0.9 / Ti 0%	
	Spacer	Polyethylene	
J	Step Plates	Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0%	
К	Rear Rung	Round: Alloy 6060 / Mg 0.35-0.6 / Ti 0.10%	
	Rivets	Zinc Plated Low Carbon Steel	
	Nuts	Plated Mild Steel with gold passivate	
	Washers	Plated Mild Steel with gold passivate	

Product Code	FPL-AT 2.4
Manufacturer's Name	Branach Manufacturing Pty Ltd
Phone Number	+61 3 9761 6633
Certified By (Name, Title)	Mike Walsh Chief Design Engineer
Last Updated	11/07/2024



