WorkMaster 450mm Step Platform FPL-AT 3.0

Technical Data Sheet

| PROPERTIES | | | |
|---------------------------------------|--|--|--|
| AS/NZS 1892.3 / ANSI A 14.5-2000 | | | |
| 150kg | | | |
| Complies to AS/NZS 1892.3 Section 2.4 | | | |
| 130 Degrees Celsius | | | |
| Tested to AS/NZS 1892.3 | | | |
| Tested to AS 2331.3.1 | | | |
| 3 years from date of manufacturing | | | |
| | | | |

MEASUREMENTS

| Â | Weight | 31.6kg |
|-------------------|------------------------|-------------------------------------|
| | Distance Between Rungs | 0.305m |
| \$ | Open Height | 3.82m |
| * | Closed Height | 4.11m |
| _ | Platform Height | 3.0m |
| \Box | Handrail Height | 0.9m above platform |
| >< | Closed Width | 0.2m |
| I<>I | Width with Satbilisers | Extended 0.93m/Fully Extended 1.32m |
| ~ | Number of Steps | 10 including platform |

COMPONENTS

| Fibreglass: ISO-PE resin with e-glass fibres |
|--|
| Round: Alloy 6060 / Mg 0.35-0.6 / Ti 0.10% |
| 35% GF Nylon / Poly Urethane Tread |
| Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0% |
| Alloy 5083-H116 / Mg 4.0-4.9 / Ti 0-0.15% |
| Alloy 6463-T6 / Mg 0.3-0.9 / Ti 0% |
| Alloy 5083-H116 / Mg 4.0-4.9 / Ti 0-0.15% |
| Alloy 6463-T6 / Mg 0.3-0.9 / Ti 0% |
| Polyethylene |
| Alloy 5052/5251 / Mg 2.2-2.8 / Ti 0% |
| Round: Alloy 6060 / Mg 0.35-0.6 / Ti 0.10% |
| Zinc Plated Low Carbon Steel |
| Plated Mild Steel with gold passivate |
| Plated Mild Steel with gold passivate |
| |

| Product Code | FPL-AT 3.0 |
|-------------------------------|-------------------------------------|
| Manufacturer's Name | Branach Manufacturing Pty Ltd |
| Phone Number | +61 3 9761 6633 |
| Certified By (Name, Title) | Mike Walsh Chief Design Engineer |
| Last Updated | 11/07/2024 |



